

KINGFISHER

Fiber Optic Microphone SOM(4) High SNR EXTF



Features

- Small, lightweight MEMS design
- Absolute EMI/RFI immunity
- Extended frequency response
- High SNR over long distances
- Noise levels lower than ECM electret microphones
- Suitable for use at extreme temperatures
- High reliability and environmental stability
- Optical fiber connection over extended lengths without signal loss



Applications

- Extreme environments requiring high fidelity monitoring
- Close-proximity machine monitoring
- Extremely low level noise monitoring
- Long range peer-to-peer monitoring
- High voltage electrical utilities
- High RFI & EMI areas
- Petrochemical facilities



Miniature optical microphone for acoustic monitoring with extended frequency response, high SNR over long distances and at extreme temperatures. Ideal where the footprint for microphone placement is severely limited or where the microphone is a sub-component in another device or system.

The SOM(4) High SNR EXTF system comprises of an advanced fiber optic microphone & single-channel electro-optic unit (EOU200), for digital-to-analog conversion of optical microphone output signals. The Single Channel EOU 200 with enhanced electronics box. It features two analog outputs (one with volume control for headphones, another with fixed gain for monitoring equipment); one pair of ST-style fiber optic connectors; two 3.5 mm sockets (one for analog output, another for headphones); green/red LED voltage indicator. DSP model provides up to 22 dB of real-time ambient noise removal (three levels: low, mid, high). Unit is powered either by internal battery or external DC power supply.

The SOM(4) High SNR EXTF is supplied as standard with clear 1mm PVC fiber-optic cable. Where there is no benefit in the thin, transparent 1mm PVC cable, we recommend the more robust Kevlar reinforced black 3mm PVC cable.

Technology

It's built around a tiny MEMS membrane and two optical fibers. When acoustic waves impinge on the membrane they cause it to vibrate, changing the intensity of light that is reflected from incoming to outgoing fibers. This patented mechanism detects even the slightest changes in membrane displacement, with resolutions at a fraction of an Angstrom. Such precision translates to clear sound and low self-noise, and produces exceptional microphone performance. ■



Technical Specifications

Polar Pattern	Omnidirectional		
Frequency Response	10-15,000Hz		
Conformity 10 – 1,000Hz	±0.5dB		
Conformity 1,000 – 15,000Hz	±3.0dB		
Sensitivity	100mV/Pa ±10% at 1kHz		
Equivalent Self-Noise Levels	≤19dBA	≤21dBA	≤34dBA
At Distances	10m	100m	1000m
Maximum Acoustic Pressure	114dB SPL		
Total Harmonic Distortion	<1% at 84dB SPL		
Equivalent Vibration Sensitivity	Max. 45dB SPL/g at 1kHz		
Supply Voltage	8-15V DC		
Current Drain (max.)	110mA		
Operating Temperature	-50 to +120°C (-58 to +248°F)		
Storage Temperature	-50 to +120°C (-58 to +248°F)		
Humidity – 1000 hours	Up to 95% RH at +40°C		
MTBF	>100,000 hours		
Microphone Head			
Material	Polycarbonate		
Dimensions D/L	6/23mm		
Weight	0.6g		
Type of Fiber Optic Cable	Multimode 100µm		
Optical Cable Length	10m standard (lengths available up to 1km)		

Product Codes

KINGFISHER SOM(4) High SNR EXTF – Full Systems

- 3-299-631*** SOM(4)SNREXTF010XT - Security Optical Microphone with 10 meters of 1mm PVC coated optical fiber no extension tube
- 3-299-632*** SOM(4)SNREXTF020XT - Security Optical Microphone with 20 meters of 1mm PVC coated optical fiber no extension tube

*All kits come as standard with: Electro Optical Unit (EOU200), Audio cable with 3.5mm jack, 8-12V DC power adapter & Guidance Manual

The SOM(4) High SNR EXTF can be supplied with Black 3mm Kevlar reinforced cable instead of the 1mm clear PVC cable at no extra cost. Kevlar cable temp. range -25 to +80°C.

KINGFISHER SOM(4) Accessories, Components & Upgrades

- 3-229-646** Extension Cable Type Outdoor, **5mm Millspec MIL STD** (specify length from 10-1000m)
- 3-299-647** Extension Cable Type Outdoor, **5.1mm Polyamide, lightweight, rigid** (specify length from 10-1000m)
- 3-299-648** Extension Cable Type Indoor, **3mm Kevlar reinforced** (specify length from 10-1000m)
- 3-299-649** Extension Cable Type Indoor, **2x3mm Zip Cord** (specify length from 10-1000m) will withstand bending and stepping on it
- 3-299-690** OPTIClear Software - PC Based speech enhancement utilizing a single channel noise reduction algorithm. OPTIClear works in both real-time and post-processing modes. Price for 1 license includes USB dongle
- 3-299-654** EOU200 + DSP (instead of EOU200) - **Built-in noise canceling via DSP**

For further information contact

Winkelmann (UK) Limited
Unit 63, Rowfant Business Centre
Wallage Lane, Rowfant, Near Crawley
West Sussex RH10 4NQ UK

T: +44 (0) 1342 719024
F: +44 (0) 1342 719030
E: sales@winkelmann.co.uk
www.winkelmann.co.uk