

KINGFISHER

Fiber Optic Microphone SOM(5) High SNR



FEATURES

- Robust design suited to industrial applications
- Absolute EMI/RFI immunity
- Completely passive sensor with no metal or electrical parts
- High SNR over long distances
- Noise levels lower than best electret microphones
- High reliability and environmental stability
- Optical fiber connection over extended lengths without signal loss
- Exceptionally low sensitivity to vibration



APPLICATIONS

- Extremely low level noise monitoring
- Long range peer-to-peer monitoring
- 'No interference' signal monitoring
- Oil and gas detection sites
- High voltage electrical utilities
- Highly explosive areas
- High RFI and EMI areas



Fiber optic microphone for indoor and outdoor acoustic monitoring that requires high signal-to-noise ratios (SNR) over extended distances. Ideal for industrial use, placement in heavy machinery, or where the microphone requires very robust housing and fiber cables.

The SOM(5) High SNR system comprises of an advanced fiber optic microphone & single-channel electro-optic unit (EOU200), for digital-to-analog conversion of optical microphone output signals. The Single Channel EOU 200 with enhanced electronics box. It features two analog outputs (one with volume control for headphones, another with fixed gain for monitoring equipment); one pair of ST-style fiber optic connectors; two 3.5 mm sockets (one for analog output, another for headphones); green/red LED voltage indicator. DSP model provides up to 22 dB of real-time ambient noise removal (three levels: low, mid, high). Unit is powered either by internal battery or external DC power supply.

TECHNOLOGY

It's built around a tiny MEMS membrane and two optical fibers. When acoustic waves impinge on the membrane they cause it to vibrate, changing the intensity of light that is reflected from incoming to outgoing fibers. This patented mechanism detects even the slightest changes in membrane displacement, with resolutions at a fraction of an Angstrom. Such precision translates to clear sound and low self-noise, and produces exceptional microphone performance. ■

TECHNICAL SPECIFICATIONS

Polar Pattern	Omnidirectional		
Frequency Response	10-10,000 Hz		
Conformity 10 - 1,000 Hz	±0.5 dB		
Conformity 1,000 - 10,000 Hz	±3.0 dB		
Sensitivity	100 mV/Pa ±10% at 1 kHz		
Equivalent Self-Noise Levels	≤19 dBA	≤21 dBA	≤34 dBA
At Distances	10 m	100 m	1000 m
Maximum Acoustic Pressure	114 dB SPL		
Total Harmonic Distortion	<1% at 84 dB SPL		
Equivalent Vibration Sensitivity	Max. 45 dB SPL/g at 1 kHz		
Supply Voltage	8-15 V DC		
Current Drain (max.)	110 mA		
Operating Temperature	-20 to +60 °C (-4 to +140 °F)		
Storage Temperature	-20 to +60 °C (-4 to +140 °F)		
Humidity - 1000 hours	Up to 95% RH at +40 °C		
MTBF	>100,000 hours		
Microphone Head			
Material	Delrin		
Dimensions D/L	10/70 mm		
Weight	5 g		
Type of Fiber Optic Cable	Multimode 100µm		
Optical Cable Length	10 m standard (lengths available up to 1km)		

PRODUCT CODES

KINGFISHER SOM(5)High SNR – Full Systems

- | | |
|------------------|--|
| 3-299-655 | SOM(5)SNR010XT - Security Optical Microphone with 10 meters of 5.1mm Black Polyamide optic cable no extension tube, Electro Optical Unit (EOU200), Audio cable with 3.5mm jack, 8-12V DC power adapter & Guidance Manual |
| 3-299-656 | SOM(5)SNR020XT - Security Optical Microphone with 20 meters of 5.1mm Black Polyamide optic cable no extension tube, Electro Optical Unit (EOU200), Audio cable with 3.5mm jack, 8-12V DC power adapter & Guidance Manual |

KINGFISHER SOM(5) Accessories, Components & Upgrades

- | | |
|------------------|---|
| 3-229-646 | Extension Cable Type Outdoor, 5mm Millspec MIL STD (specify length from 10-100m) |
| 3-299-647 | Extension Cable Type Outdoor, 5.1mm Polyamide, lightweight, rigid (specify length from 10-100m) |
| 3-299-690 | OPTIClear Software - PC Based speech enhancement utilizing a single channel noise reduction algorithm. OPTIClear works in both real-time and post-processing modes. Price for 1 license includes USB dongle |
| 3-299-654 | EOU200 + DSP (instead of EOU200)
- Built-in noise canceling via DSP |

For further information contact

Winkelmann (UK) Limited
Unit 63, Rowfant Business Centre
Wallage Lane, Rowfant, Near Crawley
West Sussex RH10 4NQ UK

T: +44 (0) 1342 719024
F: +44 (0) 1342 719030
E: sales@winkelmann.co.uk
www.winkelmann.co.uk

